



Product Specification Sheet

Heat Shrink and Preservation Tape

Heat Shrink Tape

Heat shrink tape is a polyethylene backed tape with very good adhesion which is used for repairing holes in poly film, taping on zipper access doors, and taping pleats on the shrink wrap. It may leave an adhesive residue after long term usage. Available in blue, white, and clear in widths of 2", 3", 4", and 6"; standard roll length is 180'.



Preservation Tape

Preservation tape is a conformable, tough, waterproof tape with a permanently tacky adhesive that bonds well to most surfaces over a wide range of temperatures. Includes UV inhibitors to limit adhesive residue after long term storage. Low temperature bond is very good and it is available in blue, white, and clear in widths of 2", 3", and 4"; standard roll length is 108'.

Although preservation tape is designed not to leave a residue, the adhesion is very strong to most surfaces and it is possible that the top layer of paint or finish can come off of painted surfaces or wood. Please test a small area before applying to entire surface.

Composition

Oriented Polyethylene
 Synthetic rubber-clear
 9 mil
 32 ounce/inch width
 70 ounce/inch width
 9000 volts
 Excellent
 +32° F - +160 ° F
 .4 gm/100 in²/24 hours
 100%

Backing
Adhesive
Total thickness
Adhesion to backing
Adhesion to steel
Dielectric strength
Moisture resistance
Temperature range
Water vapor trans. rate
Elongation

Composition

Oriented Polyethylene
 Synthetic rubber-clear
 10 mil
 36 ounce/inch width
 60 ounce/inch width
 9000 volts
 Excellent
 +32° F - +160 ° F
 .4 gm/100 in²/24 hours
 100%

INTERNATIONAL SHRINKWRAP SUPPLIER

www.dr-shrink.com

P: (800) 968-5147
 P: (231) 723-2685 (Outside U.S.)
 F: (231) 723-9586

Dr. Shrink+

315 Washington St.
 Manistee, Michigan 49660-1855