Product Specification Sheet

Heat Shrink and Preservation Tape

Heat Shrink Tape

Heat shrink tape is a polyethylene backed tape with very good adhesion which is used for repairing holes in poly film, taping on zipper access doors, and taping pleats on the shrink wrap. It may leave an adhesive residue after long term usage. Available in blue, white, and clear in widths of 2", 3". 4", and 6"; standard roll length is 180'.

Preservation Tape

Preservation tape is a conformable, tough, waterproof tape with a permanently tacky adhesive that bonds well to most surfaces over a wide range of temperatures. Includes UV inhibitors to limit adhesive residue after long term storage. Low temperature bond is very good and it is available in blue, white, and clear in widths of 2", 3", and 4"; standard roll length is 108'.

Although preservation tape is designed not to leave a residue, the adhesion is very strong to most surfaces and it is possible that the top layer of paint or finish can come off of painted surfaces or wood. Please test a small area before applying to entire surface.

Composition		Composition
Oriented Polyethylene	Backing	Oriented Polyethylene
Synthetic rubber-clear	Adhesive	Synthetic rubber-clear
9 mil	Total thickness	10 mil
32 ounce/inch width	Adhesion to backing	36 ounce/inch width
70 ounce/inch width	Adhesion to steel	60 ounce/inch width
9000 volts	Dielectric strength	9000 volts
Excellent	Moisture resistance	Excellent
+32° F - +160 ° F	Temperature range	+32° F - +160 ° F
.4 gm/100 in^2/24 hours	Water vapor trans. rate	.4 gm/100 in^2/24 hours
100%	Elongation	100%

INTERNATIONAL SHRINKWRAP SUPPLIER
www.dr-shrink.com
P: (800) 968-5147
P: (231) 723-2685 (Outside U.S.)
F: (231) 723-9586
Dr.Shrink
315 Washington St.
Manistee, Michigan 49660-1855